

OPUS-4700 Series

Credit Card Exit Terminal



Shown with optional EMV Terminal.

The OPUS-4700 Series Credit Card Exit Terminal communicates with Pro+ and utilizes an encrypted 2D data matrix barcode for expedited exit from parking facilities. The OPUS-4700 Series offers intuitive user guidance through a dynamic color display and voice announcement. The Exit Terminal processes encrypted thermal 2D barcode tickets from the OPUS-2000/2700 Series Entry Terminals, OPUS-4800 Credit Card Pay-on-Foot Station, OPUS-7800 Central Pay-on-Foot Station or OPUS-5000 Series Central Cashier POS Terminal. Additional options include credit card out for credit card in/out applications when used online and in conjunction with an OPUS-2700 Entry Terminal. Payment options include validations and credit card. Mobile credentials and printed barcode validations or passes can be processed through the optional FlexScan QR400® barcode scanner.


Features

- Models include standard magstripe (MSR) or PCI P2PE EMV-ready MSR/chip terminal versions
- Credential tracking support
- Illuminated components for ease-of-use
- 5.7" color display - sunlight readable
- Voice announcement and intercom
- TCP/IP network connectivity
- Thermal receipt printer with auto retract
- Textured powder coat finish
- Supports online and offline fee calculation
- Supports Roving Cashier when used with the optional proximity kit and Pro+ Roving Cashier module
- Digital ticket image is captured upon completion of the transaction
- Compatible with Genetec LPR system for lost and swapped tickets, as well as paid ticket recognition

OPUSSeries®

OPUS-4700 Series

Credit Card Exit Terminal



SPECIFICATIONS

COMPLIANCE

RoHS Compliant

The OPUS-4700 does not store credit card data

Meets ADA (Americans with Disabilities Act) and ANSI (American National Standards Institute) requirements

ELECTRICAL

Power Source: 120 VAC, 60 Hz

Utilization: 10 amp maximum (120V)

TIME CONTROL

Real-time clock synchronization with host computer

ENVIRONMENT

Temperature: -20°F ~ 120°F (-29°C ~ 49°C)
Automatic thermostat-controlled heater included

Humidity: 10% ~ 90% (non-condensing)

HOUSING

Heavy-duty, 14-gauge steel construction, weather gasketing, lockable door

Height: 51.6" (131.1 cm)

Width: 14.0" (35.6 cm)

Depth: 19.18" (48.7 cm)

Weight: 140 lbs. (63.5 kg)

Ticket throat: 41.27" (104.8 cm)

Finish (Standard): Textured powder coat finish OPUS (RAL#7022); custom color available

TICKET READER/ENCODING MECHANISM

Reads all accepted 2D data matrix barcode tickets and validation coupons

Easy ticket jam removal

Encodes encrypted 2D data matrix barcode and transaction data in man-readable text

Vaults used exit tickets

RECEIPT PRINTER

High speed thermal line dot

8" thermal paper roll

Auto-retract

INTERCOM/VOICE ANNOUNCEMENT

Aiphone LEF series intercom

Standard Voice Announcement

OPTIONAL KITS

Integrated IP Camera

Integrated FlexScan QR400 Barcode Scanner

Integrated Proximity Reader

Third-party Intercom Mounting

Specifications are approximate and are subject to change without notice.

