

PRO+ 7700 Series

Pay-in-Lane Exit Station



Shown with optional EMV Terminal.

The Pro+ 7700 Series Pay-in-Lane Exit Station communicates with Pro+ Software and is designed for flexibility and ease-of-use in any facility. The fully functional, touch screen-controlled device utilizes the latest architecture to deliver accelerated system processes and transaction speeds, making it the perfect solution for 24/7 unattended operations. The Pay-in-Lane Exit Station processes encrypted 2D data matrix barcode tickets from the Pro+ 2000/2700 Series Entry Terminals. Payment options include credit card, bills, coins, and validations. Other payment options include credit card-out for credit card-in/out applications when used online and in conjunction with an Pro+ 2700 Entry Terminal. Mobile credentials and printed barcode validations can also be processed through the optional FlexScan QR400® barcode scanner.


Features

- Models include standard magstripe (MSR) or PCI P2PE EMV-ready MSR/chip terminal versions
- Contactless credit card options for NFC, Apple Pay, and Google Pay
- 10.4" color touch screen display - sunlight readable
- Banknote recycler
- Voice announcement and intercom
- Thermal receipt printer with auto-retract
- Credential tracking support
- Illuminated components for ease-of-use
- TCP/IP network connectivity
- Supports online and offline fee calculation
- Remote device programming
- Proximity access reader, barcode scanner, and Bluetooth options
- LPR-capable and includes lost ticket calculation
- Multiple models are available to meet various configurations including credit card reader, currency, and with or without coin acceptor/recycler
- Digital ticket image captured upon completion of transaction



PRO+ 7700 Series

Pay-in-Lane Exit Station



SPECIFICATIONS

COMPLIANCE

RoHS Compliant

Pro+ 7700 Pay-in-Lane Exit Station does not store credit card data

Meets ADA (Americans with Disabilities Act) and ANSI (American National Standards Institute) requirements

ELECTRICAL

Power Source: 120 VAC, 60 Hz

Utilization: 12 amp maximum

TIME CONTROL

Real-time clock synchronization with host computer

ENVIRONMENT

Temperature: -20°F ~ 120°F (-29°C ~ 49°C)
Automatic thermostat-controlled heater included

Humidity: 10% ~ 90% (non-condensing)

HOUSING

Height: 60.22" (152.9 cm)

Width: 24.53" (62.3 cm)

Depth: 24.72" (62.7 cm)

Weight: 390 lbs. (177 kg)

Construction: Sheet steel housing

Cabinet finish: Textured powder coat finish Amano Light Gray (RAL#7047)
Custom color available

TICKET READER/ENCODING MECHANISM

Reads all accepted 2D data matrix barcode tickets and validation coupons

Easy ticket jam removal

Encodes encrypted 2D data matrix barcode data and transaction data in man-readable text

Vaults used exit tickets

RECEIPT PRINTER

High speed thermal line dot

8" thermal paper roll

Auto-retract

SECURITY

Multi-point safety lock system

Intruder alarm

Security locks on money handling compartments

INTERCOM/VOICE ANNOUNCEMENT

Aiphone™ LEF series intercom

Standard voice announcement

VERSIONS

Various currencies

PCI P2PE EMV-ready credit card terminal

With or without coin acceptor/recycler (U.S.)

OPTIONAL KITS

Integrated IP Camera

Integrated FlexScan QR400 Barcode Scanner

Integrated Proximity Reader

Third-party Intercom Mounting

(2) Coin hoppers (U.S. version); standard in Canadian version

Specifications are approximate and are subject to change without notice.

