

PRO+ 4700 Series

Credit Card Exit Terminal



Shown with optional EMV Terminal.

The Pro+ 4700 Series Credit Card Exit Terminal utilizes an encrypted 2D data matrix barcode and the latest architecture to deliver accelerated system processes and transaction speeds. The Pro+ 4700 Series communicates with Pro+ Software and offers intuitive user guidance through a dynamic color display and voice announcement. The Exit Terminal processes encrypted thermal 2D barcode tickets from the Pro+ 2000/2700 Series Entry Terminals, Pro+ 4800 Credit Card Pay-on-Foot Station, Pro+ 7800 Central Pay-on-Foot Station, or Pro+ 5000 Series Central Cashier POS Terminal. Additional options include credit card-out for credit card-in/out applications when used online and in conjunction with a Pro+ 2700 Entry Terminal. Payment options include validations and credit card. Mobile credentials and printed barcode validations or passes can be processed through the optional FlexScan QR400® barcode scanner.


Features

- Models include standard magstripe (MSR) or PCI P2PE EMV-ready MSR/chip terminal versions
- Contactless credit card options for NFC, Apple Pay, and Google Pay
- Credential tracking support
- Illuminated components for ease-of-use
- 5.7" color display - sunlight readable
- Voice announcement and intercom
- TCP/IP network connectivity
- Thermal receipt printer with auto-retract
- Remote device programming
- Proximity access reader, barcode scanner, and Bluetooth options
- LPR-capable and includes lost ticket calculation
- Supports Roving Cashier when used with the optional proximity kit and Pro+ Roving Cashier module
- Digital ticket image captured upon completion of transaction



PRO+ 4700 Series

Credit Card Exit Terminal



SPECIFICATIONS

COMPLIANCE

RoHS Compliant

The Pro+ 4700 does not store credit card data

Meets ADA (Americans with Disabilities Act) and ANSI (American National Standards Institute) requirements

ELECTRICAL

Power Source: 120 VAC, 60 Hz

Utilization: 10 amp maximum (120V)

TIME CONTROL

Real-time clock synchronization with host computer

ENVIRONMENT

Temperature: -20°F ~ 120°F (-29°C ~ 49°C)
Automatic thermostat-controlled heater included

Humidity: 10% ~ 90% (non-condensing)

HOUSING

Heavy-duty, 14-gauge steel construction, weather gasketing, lockable door

Height: 51.6" (131.1 cm)

Width: 14.0" (35.6 cm)

Depth: 19.18" (48.7 cm)

Weight: 140 lbs. (63.5 kg)

Ticket throat: 41.27" (104.8 cm)

Finish (Standard): Textured powder coat finish Amano Light Gray (RAL#7047)
Custom color available

TICKET READER/ENCODING MECHANISM

Reads all accepted 2D data matrix barcode tickets and validation coupons

Easy ticket jam removal

Encodes encrypted 2D data matrix barcode and transaction data in man-readable text

Vaults used exit tickets

RECEIPT PRINTER

High speed thermal line dot

8" thermal paper roll

Auto-retract

INTERCOM/VOICE ANNOUNCEMENT

Aiphone LEF series intercom

Standard Voice Announcement

OPTIONAL KITS

Integrated IP Camera

Integrated FlexScan QR400 Barcode Scanner

Integrated Proximity Reader

Third-party Intercom Mounting

Specifications are approximate and are subject to change without notice.

